

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number  
WO 2005/040665 A1

(51) International Patent Classification<sup>7</sup>: F16N 15/00, 39/04, 29/00

(74) Agent: RADÜNZ, Ingo; Schumannstrasse 100, 40237 Düsseldorf (DE).

(21) International Application Number:

PCT/EP2004/004360

(22) International Filing Date: 24 April 2004 (24.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
MI2003A002071 23 October 2003 (23.10.2003) IT

(71) Applicant (for all designated States except US): RAVARINI CASTOLDI & C. S.R.L. [IT/IT]; Via Gardone, 20, I-20139 Milano (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): RAVARINI, Luigi [IT/IT]; Via Massena 18, I-20145 Milano (IT).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR HEATING AND MELTING SOLID LUBRICANTS IN THE DELIVERY DRUM

(57) Abstract: An apparatus for heating and melting solid lubricants in the delivery drum (4), wherein a heating element (1) bearing down on the upper surface (3) of the product and progressively sinking into it causes the liquefaction process, and wherein by means of sensors (5 and 7) the temperatures required for liquefaction and for maintaining the liquid state are regulated.



WO 2005/040665 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, — *with amended claims*  
GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*